VISOR® V20 Code Reader Standard, medium field of view

Reading of 1D and 2D codes



PRODUCT HIGHLIGHTS

- Can be used for all common 2D codes (ECC 200 data matrix) and common 1D barcodes
- Comprehensive tools for flexible and easy connection to PC and PLC environments

Optical data	
Resolution	1440 x 1080 pixels
Imaging chip CMOS	1/2.9", monochrome
Integrated lens, focal length [mm]	12 (medium)
Pixel size	3.45 µm x 3.45 µm
Focus	Motorized
Adjustment range	25 mm to infinity
Integrated illumination	White (5000 K), red (635 nm), infrared (850 nm) LEDs
Minimum field of view, X x Y	10 x 8 mm
Target laser	Laser: red (635 nm) class 1 (IEC 60825-1)

Functions	
Number of jobs / detectors	8 / 2
Detectors	**Barcode:** reading 1D barcodes; EAN, UPC, RSS, 2/5 Interleaved, 2/5 Industrial, code 32, code 39, code 93, code 128, ECC200 GS1, pharm code, codabar; **Datacode:** reading 2D codes: ECC200 (GS1), QR code (GS1), Micro QR code, Aztec code (GS1), PDF 417;


Electrical data	
Operating voltage, $+U_B$	18 ... 30 DC[1]
Current consumption (without I/O)	≤ 300 mA
Protective circuits	Reverse-polarity protection, U_B / short-circuit protection of all outputs
Power On Delay	Approx. 13 s after Power on
Outputs	PNP/NPN (switchable)
Max. output current (per output)	50 mA, 100 mA (pin 12)
Switching threshold inputs incl. encoder	PNP/NPN High > U_B-1 V / Low < 3 V
Input resistance	> 20 kΩ
Interfaces VISOR® V20-CR-Advanced	Ethernet (LAN), EtherNet/IP, PROFINET, SensoWeb, Service Port
Inputs/outputs	2 inputs, 2 outputs, 6 selectable inputs/outputs
Encoder	✓

Mechanical data	
Dimensions	70.4 x 45 x 45 mm (without plug)
Enclosure rating	IP 67 & IP 65
Material, housing	Aluminium, die-cast, RoHS compliant
Material, front screen	Plastic
Ambient temperature: operation	0 … +50 °C[2]
Ambient temperature: storage	-20 … +60 °C[2]
Weight	Approx. 200 g
Plug connections	Supply and I/O M12, 12-pin Ethernet M12, 4-pin
Vibration resistance	EN 60068-2-6
Shock resistance	EN 60068-2-27


[1] Max. ripple < 5 V_{SS} [2] 80 % air humidity, noncondensing

Version: 04/2022. Subject to changes; diagrams similar

VISOR® vision sensor



Field of view V20, medium



- - - - - Increased depth of field
——— Normal depth of field

Illumination	Part number	Article number	Accessories	
White	V20-CR-S3-W-M-M2-L	632-91056	Connection cables	www.sensopart.com/en/accessories
Red	V20-CR-S3-R-M-M2-L	632-91059	Illumination	
Infrared	V20-CR-S3-I-M-M2-L	632-91062	Brackets	
			Interface accessories	